

Adaptador Storz x Macho Rigido - MSA

Storz x Macho NST (NH)

Medida Storz	Macho NST (NH)	Aluminio Forjado 6061-T6 # de Parte
1½"	1½"	MSA1515F
2"	1½"	MSA2015F
2½"	2½"	MSA2525F
3"	2½"	MSA3025F
4"	2½"	MSA4025F
	4"	MSA4040F
	4½"	MSA4045F
5"	2½"	MSA5025F
	5"	MSA5050F



Storz x Macho NPT

Medida Storz	Rosca Macho NPT	Aluminio Forjado 6061-T6 # de Parte
1½"	1½"	MSA1515T
2"	1½"	MSA2015T
2½"	2"	MSA2520T
	2½"	MSA2525T
	3"	MSA2530T
3"	3"	MSA3030T
4"	4½"	MSA4025T
	4"	MSA4040T
5"	4"	MSA5040T
6"	6"	MSA6060T



Storz x Macho NPSH

Medida Storz	Rosca Macho NPSH	Aluminio Forjado 6061-T6 # de Parte
1½"	1½"	MSA1515S
2"	1½"	MSA2015S



1½" x 1½"

Conexión Giratoria Storz - SLSA

Especificación:

- Presión de trabajo: 200 PSI a 70°F (21°C).

Storz	FNPT	Aluminio Forjado 6061-T6 # de Parte
4"	4"	SLSA4040T
5"		SLSA5040T



NOTA: Para configuraciones de 2-1/2" a 6" de extremos distintos a Storz.

