

Serie-K Coples Hidráulicos

Opciones Disponibles

Medida	Opciones de Sello Estándar						Opciones de Sello Kalrez®		
	FKM	EPDM	FDA FKM	Mil-Nitrilo	Combustible Nitrilo	Silicón	4079	6375	7075
1/4"	F-	P-	D-	M-	JF-	S-	K4-	K6-	K7-
3/8"	F-	P-	D-	M-	JF-	S-	K4-	K6-	K7-
1/2"	F-	P-	D-	M-	JF-	S-	K4-	K6-	K7-
3/4"	F-	P-	D-	M-	JF-	S-	K4-	K6-	K7-
1"	F-	P-	D-	M-	JF-	S-	K4-	K6-	K7-
1-1/4"	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
1-1/2"	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
2"	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Medida	Opciones de Válvula						Manga	Tratamiento
	Sin Válvula	Actuador ¹	Acero	Latón	Al 303	Al 316	Seguridad	Oxy-Clean
1/4"	-E	N/A	-ZV	-BV	N/A	N/A	-LS	-C1
3/8"	-E	-VA	-ZV	-BV	-SV	SSV	-LS	-C1
1/2"	-E	-VA	-ZV	-BV	-SV	SSV	-LS	-C1
3/4"	-E	-VA	-ZV	-BV	-SV	SSV	-LS	-C1
1"	-E	-VA	-ZV	-BV	-SV	SSV	-LS	-C1
1-1/4"	N/A	N/A	-ZV	N/A	N/A	N/A	N/A	N/A
1-1/2"	N/A	N/A	-ZV	N/A	N/A	N/A	N/A	N/A
2"	N/A	N/A	-ZV	N/A	N/A	N/A	N/A	N/A

¹ Actuador de válvula de latón.



Serie - K Cople Intercambio ISO - A (Rosca Hembra)

Medida	Detalle			Medida		D.E. Máximo		Hex pulg.
	# de Parte	Roscas	Material	pulg.	mm.	pulg.	mm.	
1/4"	2KF1	1/8" - 27 NPTF	Acero	1.89	47.9	1.00	25.4	3/4"
	2KF2	1/4" - 18 NPTF	Acero	1.89	47.9	1.00	25.4	3/4"
	2KF2-SS	1/4" - 18 NPTF	A.I. 316	1.89	47.9	1.00	25.4	3/4"
	2KBF2	1/4" - 19 BSPP	Acero	1.89	47.9	1.00	25.4	3/4"
	2KBF2-SS	1/4" - 19 BSPP	A.I. 316	1.89	47.9	1.00	25.4	3/4"
	2KOF2	7/16" - 20 ORB	Acero	1.89	47.9	1.00	25.4	3/4"
3/8"	3KF3	3/8" - 18 NPTF	Acero	2.23	56.5	1.19	30.2	7/8"
	3KF3-SS	3/8" - 18 NPTF	A.I. 316	2.23	56.5	1.19	30.2	7/8"
	3KBF3	3/8" - 19 BSPP	Acero	2.23	56.6	1.19	30.2	7/8"
	3KBF3-SS	3/8" - 19 BSPP	A.I. 316	2.23	56.6	1.19	30.2	7/8"
	3KOF3	9/16" - 18 ORB	Acero	2.23	56.6	1.19	30.2	7/8"
1/2"	4KF4	1/2" - 14 NPTF	Acero	2.62	66.5	1.49	37.8	1-1/16"
	4KF4-SS	1/2" - 14 NPTF	A.I. 316	2.62	66.5	1.49	37.8	1-1/16"
	4KBF4	1/2" - 14 BSPP	Acero	2.62	66.5	1.49	37.8	1-1/16"
	4KBF4-SS	1/2" - 14 BSPP	A.I. 316	2.62	66.5	1.49	37.8	1-1/16"
	4KOF4	3/4" - 16 ORB	Acero	2.62	66.5	1.49	37.8	1-1/16"
	4KOF5	7/8" - 14 ORB	Acero	2.66	67.6	1.49	37.8	1-3/32"
	4KF6	3/4" - 14 NPTF	Acero	2.64	66.9	1.49	37.8	1-5/16"



Acero / acero inoxidable 316