


Acoples de Latón de Vástago Corto - Rosca NPSM

Usar arandelas KRW de la página 284.

Acople Completo Maquinado

D.I. Manguera	Rosca	# de Parte
1/2"	3/4"	BS406
3/4"	3/4"	BS606
1"	1"	BS808 ¹


¹ 1" tiene rosca NPSH.



Hembra con Tuerca Giratoria Maquinada

D.I. Manguera	Rosca	# de Parte
1/2"	3/4"	BS446
5/8"	3/4"	BS546
3/4"	3/4"	BS646
1"	1"	BS848 ¹

¹ 1" tiene rosca NPSH.




H

Macho Maquinado

D.I. Manguera	Rosca	# de Parte
1/2"	3/4"	BS416
3/4"	3/4"	BS616
1"	1"	BS818 ¹

¹ 1" tiene rosca NPSH.



Acople con Hexágono

Hembra NPTF

• Referencia SAE 130138.

Rosca NPTF	Latón # de Parte	Latón libre de Plomo ^{1,2} # de Parte
1/8" x 1/8"	3710202C	3710202CLF
1/4" x 1/4"	3710404C	3710404CLF
3/8" x 3/8"	3710606C	3710606CLF
1/2" x 1/2"	3710808C	3710808CLF
3/4" x 3/4"	3711212C	---
1" x 1"	3711616C	---

¹ Latón libre de plomo <=0.25% plomo, aleación CA2745; aleación C46400.

² Rosca NPT.



Acople Pasamuros

Latón # de Parte	Hembra NPTF	Tamaño de Orificio	Largo
207BH2	1/8"	5/8"	1.50"
207BH4	1/4"	3/4"	1.50"
207BH4S	1/4"	3/4"	.94"
207BH6	3/8"	1"	1.31"
207BH8	1/2"	1-1/8"	1.50"
207BH12	3/4"	1-5/16"	1.50"

