


Hembra 45° SAE/37° JIC Giratoria x Barbas para Manguera




D.I. Manguera	D.E. Tubo	Hembra UNF	Latón # de Parte
3/16"	1/4"	7/16"-20	1430307K
1/4"	1/4"	7/16"-20	1430407K
	5/16"	1/2"-20	1430407KLF ¹
5/16"	5/16"	1/2"-20	1430408K
3/8"	1/2"	3/4"-16	1430508K
1/2"	1/2"	3/4"-16	1430612K
	5/8"	7/8"-14	1430812K
			1430814K

¹ Latón libre de plomo <=0.25% plomo; aleación C2745 certificada NSF®/ANSI 61.

Hembra 45° SAE Giratoria x Barbas para Manguera


H



D.I. Manguera	D.E. Tubo	Hembra UNF	Latón # de Parte
3/16"	3/16"	3/8"-24	1440306K
1/4"	3/8"	5/8"-18	1440410K
5/16"	3/8"	5/8"-18	1440510K
3/8"	3/8"	5/8"-18	1440610K
1/2"	1/2"	3/4"-16	1440812K
3/4"	3/4"	1-1/16"-14	1441217K ¹

¹ Muesca en la tuerca para identificación SAE.

Hembra 37° JIC Giratoria x Barbas para Manguera



D.I. Manguera	D.E. Tubo	Hembra UNF	Latón # de Parte
3/8"	3/8"	9/16"-18	1450609K
3/4"	3/4"	1-1/16"-12	1451217K

Hembra PTF-SAE Corta Giratoria x Barbas para Manguera¹



D.I. Manguera	Hembra PTF-SAE Corto	Latón # de Parte
1/4"	1/4"	1050404C
	3/8"	1050406C
5/16"	1/4"	1050504C
	3/8"	1050604C
3/8"	3/8"	1050606C
	1/2"	1050806C
1/2"	1/2"	1050808C
	3/8"	1051008C
5/8"	1/2"	1051008C
3/4"	1/4"	1051204C
	1/2"	1051208C

¹ La conexión giratoria es para conveniencia solamente, no utilice como giratoria constante. Presión de operación a **80 PSI**.