

### Serie-H Coples Hidráulicos

#### Serie-H Cople Intercambio ISO-B (Rosca Hembra)

Medida	Detalle			Medida		D.E. Máximo		Hex pulg.
	# de Parte	Roscas	Material	pulg.	mm.	pulg.	mm.	
1/8"	1HF1	1/8" - 27 NPTF	Acero	1.90	48.3	0.93	23.6	9/16"
	1HF1-B	1/8" - 27 NPTF	Latón	1.90	48.3	0.93	23.6	9/16"
	1HF1-S	1/8" - 27 NPTF	A.I. 303	1.90	48.3	0.93	23.6	9/16"
	1HF1-SS	1/8" - 27 NPTF	A.I. 316	1.90	48.3	0.93	23.6	9/16"
	1HOF2	7/16" - 20 ORB	Acero	1.90	48.3	0.93	23.6	9/16"
1/4"	2HF2	1/4" - 18 NPTF	Acero	2.26	57.4	1.12	28.4	7/8"
	2HF2-B	1/4" - 18 NPTF	Latón	2.26	57.4	1.12	28.4	7/8"
	2HF2-S	1/4" - 18 NPTF	A.I. 303	2.26	57.4	1.12	28.4	7/8"
	2HF2-SS	1/4" - 18 NPTF	A.I. 316	2.26	57.4	1.12	28.4	3/4"
	2HBF2	1/4" - 19 BSPP	Acero	2.26	57.4	1.12	28.4	7/8"
	2HBF2-B	1/4" - 19 BSPP	Latón	2.26	57.4	1.12	28.4	7/8"
	2HBF2-S	1/4" - 19 BSPP	A.I. 303	2.26	57.4	1.12	28.4	7/8"
	2HBF2-SS	1/4" - 19 BSPP	A.I. 316	2.26	57.4	1.12	28.4	3/4"
	2HOF3	9/16" - 18 ORB	Acero	2.29	58.2	1.12	28.4	13/16"
	3/8"	3HF3	3/8" - 18 NPTF	Acero	2.51	63.8	1.42	36.1
3HF3-B		3/8" - 18 NPTF	Latón	2.51	63.8	1.42	36.1	1-1/16"
3HF3-S		3/8" - 18 NPTF	A.I. 303	2.51	63.8	1.42	36.1	1-1/16"
3HF3-SS		3/8" - 18 NPTF	A.I. 316	2.51	63.8	1.42	36.1	7/8"
3HBF3		3/8" - 19 BSPP	Acero	2.51	63.8	1.42	36.1	1-1/16"
3HBF3-B		3/8" - 19 BSPP	Latón	2.51	63.8	1.42	36.1	1-1/16"
3HBF3-S		3/8" - 19 BSPP	A.I. 303	2.51	63.8	1.42	36.1	1-1/16"
3HBF3-SS		3/8" - 19 BSPP	A.I. 316	2.51	63.8	1.42	36.1	7/8"
1/2"	3HOF4	3/4" - 16 ORB	Acero	2.62	66.5	1.42	36.1	1"
	4HF4	1/2" - 14 NPTF	Acero	2.86	72.6	1.86	47.2	1-5/16"
	4HF4-B	1/2" - 14 NPTF	Latón	2.86	72.6	1.86	47.2	1-5/16"
	4HF4-S	1/2" - 14 NPTF	A.I. 303	2.86	72.6	1.86	47.2	1-5/16"
	4HF4-SS	1/2" - 14 NPTF	A.I. 316	2.86	72.6	1.86	47.2	1-1/16"
	4HBF4	1/2" - 14 BSPP	Acero	2.86	72.6	1.86	47.2	1-5/16"
	4HBF4-B	1/2" - 14 BSPP	Latón	2.86	72.6	1.86	47.2	1-5/16"
	4HBF4-S	1/2" - 14 BSPP	A.I. 303	2.86	72.6	1.86	47.2	1-5/16"
	4HBF4-SS	1/2" - 14 BSPP	A.I. 316	2.86	72.6	1.86	47.2	1-1/16"
	4HOF5	7/8" - 14 ORB	Acero	2.90	73.7	1.86	47.2	1-1/8"
3/4"	6HF6	3/4" - 14 NPTF	Acero	3.55	90.2	2.22	56.4	1-5/16"
	6HF6-B	3/4" - 14 NPTF	Latón	3.55	90.2	2.22	56.4	1-5/16"
	6HF6-S	3/4" - 14 NPTF	A.I. 303	3.55	90.2	2.22	56.4	1-5/16"
	6HF6-SS	3/4" - 14 NPTF	A.I. 316	3.55	90.2	2.22	56.4	1-5/16"
	6HBF6	3/4" - 14 BSPP	Acero	3.55	90.2	2.22	56.4	1-5/16"
	6HBF6-B	3/4" - 14 BSPP	Latón	3.55	90.2	2.22	56.4	1-5/16"
	6HBF6-S	3/4" - 14 BSPP	A.I. 303	3.55	90.2	2.22	56.4	1-5/16"
	6HBF6-SS	3/4" - 14 BSPP	A.I. 316	3.55	90.2	2.22	56.4	1-5/16"
1"	6HOF6	1-1/16" - 12 ORB	Aacero	3.69	93.7	2.22	56.4	1-5/16"
	8HF8	1" - 11-1/2 NPTF	Acero	4.13	104.9	2.49	63.2	1-5/8"
	8HF8-B	1" - 11-1/2 NPTF	Latón	4.13	104.9	2.49	63.2	1-5/8"
	8HF8-S	1" - 11-1/2 NPTF	A.I. 303	4.13	104.9	2.49	63.2	1-5/8"
	8HF8-SS	1" - 11-1/2 NPTF	A.I. 316	4.13	104.9	2.49	63.2	1-5/8"
	8HBF8	1" - 11 BSPP	Acero	4.13	104.9	2.49	63.2	1-5/8"
	8HBF8-B	1" - 11 BSPP	Latón	4.13	104.9	2.49	63.2	1-5/8"
	8HBF8-S	1" - 11 BSPP	A.I. 303	4.13	104.9	2.49	63.2	1-5/8"
	8HBF8-SS	1" - 11 BSPP	A.I. 316	4.13	104.9	2.49	63.2	1-5/8"
8HOF8	1-5/16" - 12 ORB	Acero	4.19	106.3	2.49	63.2	1-5/8"	



Acero



Latón



Acero inoxidable 303

