

Serie-H Coples Hidráulicos

Serie-H Niple Intercambio ISO-B (Rosca Hembra)

Medida	Detalle			Medida		D.E. Máximo		Hex pulg.
	# de Parte	Roscas	Material	pulg.	mm.	pulg.	mm.	
1/8"	H1F1	1/8" - 27 NPTF	Acero	1.28	32.5	0.65	16.5	9/16"
	H1F1-B	1/8" - 27 NPTF	Latón	1.28	32.5	0.65	16.5	9/16"
	H1F1-S	1/8" - 27 NPTF	A.I. 303	1.28	32.5	0.65	16.5	9/16"
	H1F1-SS	1/8" - 27 NPTF	A.I. 316	1.28	32.5	0.65	16.5	9/16"
	H1OF2	7/16" - 20 ORB	Acero	1.28	32.5	0.65	16.5	9/16"
1/4"	H2F2	1/4" - 18 NPTF	Acero	1.55	39.4	0.83	21.1	3/4"
	H2F2-B	1/4" - 18 NPTF	Latón	1.55	39.4	0.83	21.1	3/4"
	H2F2-S	1/4" - 18 NPTF	A.I. 303	1.55	39.4	0.83	21.1	3/4"
	H2F2-SS	1/4" - 18 NPTF	A.I. 316	1.55	39.4	0.83	21.1	3/4"
	H2BF2	1/4" - 19 BSPP	Acero	1.55	39.4	0.83	21.1	3/4"
	H2BF2-B	1/4" - 19 BSPP	Latón	1.55	39.4	0.83	21.1	3/4"
	H2BF2-S	1/4" - 19 BSPP	A.I. 303	1.55	39.4	0.83	21.1	3/4"
	H2BF2-SS	1/4" - 19 BSPP	A.I. 316	1.55	39.4	0.83	21.1	3/4"
	H2OF3	9/16" - 18 ORB	Acero	1.61	40.9	0.90	22.9	13/16"
	3/8"	H3F3	3/8" - 18 NPTF	Acero	1.70	43.2	0.97	24.6
H3F3-B		3/8" - 18 NPTF	Latón	1.70	43.2	0.97	24.6	7/8"
H3F3-S		3/8" - 18 NPTF	A.I. 303	1.70	43.2	0.97	24.6	7/8"
H3F3-SS		3/8" - 18 NPTF	A.I. 316	1.70	43.2	0.97	24.6	7/8"
H3BF3		3/8" - 19 BSPP	Acero	1.70	43.2	0.97	24.6	7/8"
H3BF3-B		3/8" - 19 BSPP	Latón	1.70	43.2	0.97	24.6	7/8"
H3BF3-S		3/8" - 19 BSPP	A.I. 303	1.70	43.2	0.97	24.6	7/8"
H3BF3-SS		3/8" - 19 BSPP	A.I. 316	1.70	43.2	0.97	24.6	7/8"
H3OF4		3/4" - 16 ORB	Acero	1.79	45.5	1.10	27.9	1"
1/2"	H4F4	1/2" - 14 NPTF	Acero	1.94	49.3	1.17	29.7	1-1/16"
	H4F4-B	1/2" - 14 NPTF	Latón	1.94	49.3	1.17	29.7	1-1/16"
	H4F4-S	1/2" - 14 NPTF	A.I. 303	1.94	49.3	1.17	29.7	1-1/16"
	H4F4-SS	1/2" - 14 NPTF	A.I. 316	1.94	49.3	1.17	29.7	1-1/16"
	H4BF4	1/2" - 14 BSPP	Acero	1.94	49.3	1.17	29.7	1-1/16"
	H4BF4-B	1/2" - 14 BSPP	Latón	1.94	49.3	1.17	29.7	1-1/16"
	H4BF4-S	1/2" - 14 BSPP	A.I. 303	1.94	49.3	1.17	29.7	1-1/16"
	H4BF4-SS	1/2" - 14 BSPP	A.I. 316	1.94	49.3	1.17	29.7	1-1/16"
3/4"	H4OF5	7/8" - 14 ORB	Acero	1.94	49.3	1.24	31.5	1-1/8"
	H6F6	3/4" - 14 NPTF	Acero	2.44	61.2	1.50	36.6	1-3/8"
	H6F6-B	3/4" - 14 NPTF	Latón	2.44	61.2	1.50	36.6	1-3/8"
	H6F6-S	3/4" - 14 NPTF	A.I. 303	2.44	61.2	1.50	36.6	1-3/8"
	H6F6-SS	3/4" - 14 NPTF	A.I. 316	2.44	61.2	1.50	36.6	1-3/8"
	H6BF6	3/4" - 14 BSPP	Acero	2.44	61.2	1.50	36.6	1-3/8"
	H6BF6-B	3/4" - 14 BSPP	Latón	2.44	61.2	1.50	36.6	1-3/8"
	H6BF6-S	3/4" - 14 BSPP	A.I. 303	2.44	61.2	1.50	36.6	1-3/8"
	H6BF6-SS	3/4" - 14 BSPP	A.I. 316	2.44	61.2	1.50	36.6	1-3/8"
	H6OF6	1-1/16" - 12 ORB	Acero	2.58	61.2	1.50	36.6	1-3/8"
1"	H8F8	1" - 11-1/2 NPTF	Acero	2.87	72.9	1.79	45.5	1-5/8"
	H8F8-B	1" - 11-1/2 NPTF	Latón	2.87	72.9	1.79	45.5	1-5/8"
	H8F8-S	1" - 11-1/2 NPTF	A.I. 303	2.87	72.9	1.79	45.5	1-5/8"
	H8F8-SS	1" - 11-1/2 NPTF	A.I. 316	2.87	72.9	1.79	45.5	1-5/8"
	H8BF8	1" - 11 BSPP	Acero	2.87	72.9	1.79	45.5	1-5/8"
	H8BF8-B	1" - 11 BSPP	Latón	2.87	72.9	1.79	45.5	1-5/8"
	H8BF8-S	1" - 11 BSPP	A.I. 303	2.87	72.9	1.79	45.5	1-5/8"
	H8BF8-SS	1" - 11 BSPP	A.I. 316	2.87	72.9	1.79	45.5	1-5/8"
	H8OF8	1-5/16" - 12 ORB	Acero	2.87	72.9	1.79	45.5	1-5/8"



Acero



Latón



Acero inoxidable 303

K