

Serie-V Coples Hidráulicos

Serie-V Cople Con Válvula Intercambio Snap-Tite H/IH (Rosca Macho)

Medida	Detalle			Medida		D.E. Máximo		Hex pulg.
	# Parte	Roscas	Material	pulg.	mm.	pulg.	mm.	
1/4"	2VM1	1/8" - 27 NPTF	Acero	2.12	53.8	0.99	25.1	7/8"
	2VM2	1/4" - 18 NPTF	Acero	2.12	53.8	0.99	25.1	7/8"
	2VM2-B	1/4" - 18 NPTF	Latón	2.12	53.8	0.99	25.1	7/8"
	2VM2-SS	1/4" - 18 NPTF	A.I. 316	2.12	53.8	0.99	25.1	7/8"
3/8"	3VM3	3/8" - 18 NPTF	Acero	2.32	58.9	1.18	30.0	1"
	3VM3-B	3/8" - 18 NPTF	Latón	2.32	58.9	1.18	30.0	1"
	3VM3-SS	3/8" - 18 NPTF	A.I. 316	2.32	58.9	1.18	30.0	1"
1/2"	4VM4	1/2" - 14 NPTF	Acero	2.54	64.5	1.36	34.5	1-3/16"
	4VM4-B	1/2" - 14 NPTF	Latón	2.54	64.5	1.36	34.5	1-3/16"
	4VM4-SS	1/2" - 14 NPTF	A.I. 316	2.54	64.5	1.36	34.5	1-3/16"
3/4"	6VM6	3/4" - 14 NPTF	Acero	3.07	78.0	1.67	42.4	1-1/2"
	6VM6-B	3/4" - 14 NPTF	Latón	3.07	78.0	1.67	42.4	1-1/2"
	6VM6-SS	3/4" - 14 NPTF	A.I. 316	3.07	78.0	1.67	42.4	1-1/2"
1"	8VM8	1" - 11-1/2 NPTF	Acero	3.32	84.3	2.06	52.3	1-7/8"
	8VM8-B	1" - 11-1/2 NPTF	Latón	3.32	84.3	2.06	52.3	1-7/8"
	8VM8-SS	1" - 11-1/2 NPTF	A.I. 316	3.32	84.3	2.06	52.3	1-7/8"
1-1/4"	10VM10	1-1/4" - 11-1/2 NPTF	Acero	3.59	91.2	2.19	55.6	2"
	10VM10-B	1-1/4" - 11-1/2 NPTF	Latón	3.59	91.2	2.19	55.6	2"
	10VM10-SS	1-1/4" - 11-1/2 NPTF	A.I. 316	3.59	91.2	2.19	55.6	2"
1-1/2"	12VM12	1-1/2" - 11-1/2 NPTF	Acero	4.01	101.9	2.74	69.6	2-1/2"
	12VM12-B	1-1/2" - 11-1/2 NPTF	Latón	4.01	101.9	2.74	69.6	2-1/2"
	12VM12-SS	1-1/2" - 11-1/2 NPTF	A.I. 316	4.01	101.9	2.74	69.6	2-1/2"
2"	16VM16	2" - 11-1/2 NPTF	Acero	4.54	115.3	3.83	97.3	3-1/2"
	16VM16-B	2" - 11-1/2 NPTF	Latón	4.54	115.3	3.83	97.3	3-1/2"
	16VM16-SS	2" - 11-1/2 NPTF	A.I. 316	4.54	115.3	3.83	97.3	3-1/2"



Acero



Latón



Acero inoxidable 316

