

Serie-V Coples Hidráulicos

Serie-V Cople Con Válvula Intercambio Snap-Tite H/IH (Rosca Macho JIC)

Medida	Detalle			Medida		D.E. Máximo		Hex pulg.
	# Parte	Roscas	Material	pulg.	mm.	pulg.	mm.	
1/4"	2VJM2	7/16" - 20 JIC	Acero	2.12	53.8	0.99	25.1	7/8"
3/8"	3VJM3	9/16" - 18 JIC	Acero	2.32	58.9	1.18	30.0	1"
1/2"	4VJM4	3/4" - 16 JIC	Acero	2.54	64.5	1.36	34.5	1-3/16"
3/4"	6VJM6	1-1/16" - 12 JIC	Acero	3.07	78.0	1.67	42.4	1-1/2"
1"	8VJM8	1-5/16" - 12 JIC	Acero	3.32	84.3	2.06	52.3	1-7/8"
1-1/4"	10VJM10	1-5/8" - 12 JIC	Acero	3.59	91.2	2.19	55.6	2"



Acero rosca JIC

Serie-V Niple Con Válvula Intercambio Snap-Tite H/IH (Rosca Macho JIC)

Medida	Detalle			Medida		D.E. Máximo		Hex pulg.
	# Parte	Roscas	Material	pulg.	mm.	pulg.	mm.	
1/4"	V2JM2	7/16" - 20 JIC	Acero	2.06	52.3	0.97	24.6	7/8"
3/8"	V3JM3	9/16" - 18 JIC	Acero	2.25	57.2	1.1	27.9	1"
1/2"	V4JM4	3/4" - 16 JIC	Acero	2.40	61.0	1.31	33.3	1-3/16"
3/4"	V6JM6	1-1/16" - 12 JIC	Acero	2.91	73.9	1.65	41.9	1-1/2"
1"	V8JM8	1-5/16" - 12 JIC	Acero	3.22	81.8	2.06	52.3	1-7/8"
1-1/4"	V10JM10	1-5/8" - 12 JIC	Acero	3.46	87.9	2.19	55.6	2"



K