

Serie-ST Coples Hidráulicos

Medida	Opciones de Sellado Estándar				Opciones de Sello Kalrez®			Manga	Tratamiento
	FKM	EPDM	Mil-Nitrilo	Combustible Nitrilo	4079	6375	7075	Seguro	Oxy-Clean
1/4"	F-	P-	M-	JF-	K4-	K6-	K7-	-LS	-C1
3/8"	F-	P-	M-	JF-	K4-	K6-	K7-	-LS	-C1
1/2"	F-	P-	M-	JF-	K4-	K6-	K7-	-LS	-C1
3/4"	F-	P-	M-	JF-	K4-	K6-	K7-	-LS	-C1
1"	F-	P-	M-	JF-	K4-	K6-	K7-	-LS	-C1
1"-V2	F-	P-	M-	JF-	K4-	K6-	K7-	-LS	-C1
2"	F-	P-	M-	JF-	K4-	K6-	K7-	-LS	-C1

Serie-ST Cople Intercambio Snap-Tite Serie-71 (Rosca Hembra)

Medida	Detalle			Medida		D.E. Máximo		Hex pulg.
	# Parte	Roscas	Material	pulg.	mm.	pulg.	mm.	
1/4"	2STF2	1/4" - 18 NPTF	Acero	1.96	49.8	1.23	31.2	15/16"
	2STF2-SS	1/4" - 18 NPTF	A.I. 316	1.96	49.8	1.23	31.2	15/16"
	2STBF2	1/4" - 19 BSPP	Acero	1.96	49.8	1.23	31.2	15/16"
	2STBF2-SS	1/4" - 19 BSPP	A.I. 316	1.96	49.8	1.23	31.2	15/16"
3/8"	3STF2	1/4" - 18 NPTF	Acero	2.36	59.9	1.60	40.6	1-3/16"
	3STF3	3/8" - 18 NPTF	Acero	2.36	59.9	1.60	40.6	1-3/16"
	3STF3-SS	3/8" - 18 NPTF	A.I. 316	2.36	59.9	1.60	40.6	1-3/16"
	3STBF3	3/8" - 19 BSPP	Acero	2.36	59.9	1.60	40.6	1-3/16"
	3STBF3-SS	3/8" - 19 BSPP	A.I. 316	2.36	59.9	1.60	40.6	1-3/16"
	3STF4	1/2" - 14 NPTF	Acero	2.36	59.9	1.60	40.6	1-3/16"
1/2"	3STF4-SS	1/2" - 14 NPTF	A.I. 316	2.36	59.9	1.60	40.6	1-3/16"
	3STBF4	1/2" - 14 BSPP	Acero	2.36	59.9	1.60	40.6	1-3/16"
	3STBF4-SS	1/2" - 14 BSPP	A.I. 316	2.36	59.9	1.60	40.6	1-3/16"
	4STF4	1/2" - 14 NPTF	Acero	2.77	70.4	1.98	50.3	1-1/2"
	4STF4-SS	1/2" - 14 NPTF	A.I. 316	2.77	70.4	1.98	50.3	1-1/2"
	4STBF4	1/2" - 14 BSPP	Acero	2.77	70.4	1.98	50.3	1-1/2"
3/4"	4STBF4-SS	1/2" - 14 BSPP	A.I. 316	2.77	70.4	1.98	50.3	1-1/2"
	4STOF4	3/4" - 16 ORB	Acero	2.77	70.4	1.98	50.3	1-1/2"
	6STF6	3/4" - 14 NPTF	Acero	3.03	77.0	2.35	59.7	1-3/4"
	6STF6-SS	3/4" - 14 NPTF	A.I. 316	3.03	77.0	2.35	59.7	1-3/4"
	6STBF6	3/4" - 14 BSPP	Acero	3.03	77.0	2.35	59.7	1-3/4"
1"	6STBF6-SS	3/4" - 14 BSPP	A.I. 316	3.03	77.0	2.35	59.7	1-3/4"
	6STOF6	1-1/16" - 12 ORB	Acero	3.03	77.0	2.35	59.7	1-3/4"
	8STF8	1" - 11-1/2 NPTF	Acero	3.33	84.6	2.73	69.3	2"
	8STF8-SS	1" - 11-1/2 NPTF	A.I. 316	3.33	84.6	1.55	39.3	2"
	8STBF8	1" - 11 BSPP	Acero	3.33	84.6	2.73	69.3	2"
	8STBF8-SS	1" - 11 BSPP	A.I. 316	3.33	84.6	2.73	69.3	2"
	8STOF8	1-5/16" - 12 ORB	Acero	3.33	84.6	2.73	69.3	2"
	8STF10	1-1/4" - 11-1/2 NPTF	Acero	3.67	93.2	2.73	69.3	2"
	8STF10-SS	1-1/4" - 11-1/2 NPTF	A.I. 316	3.67	93.2	2.73	69.3	2"
	8STBF10	1-1/4" - 11 BSPP	Acero	3.67	93.2	2.73	69.3	2"
8STBF10-SS	1-1/4" - 11 BSPP	A.I. 316	3.67	93.2	2.73	69.3	2"	
8STOF10	1-5/8" - 12 ORB	Acero	3.67	93.2	2.73	69.3	2"	



Acero



Acero inoxidable 316

K