

Serie-WS Coples Hidráulicos

Serie-WS Cople de Alta Presión Intercambio Mariposa "Wingstyle" (Rosca Hembra)

Medida	Detalle			Medida		D.E. Máximo		Hex pulg.
	# Parte	Roscas	Material	pulg.	mm.	pulg.	mm.	
3/4"	6WSF4	1/2" - 14 NPTF	Acero	2.76	70.1	3.31	82.0	---
	6WSF6	3/4" - 14 NPTF	Acero	2.76	70.1	3.31	82.0	---
	6WSF6-SS	3/4" - 14 NPTF	A.I. 316	2.76	70.1	3.31	82.0	---
	6WSBF6	3/4" - 14 BSPP	Acero	2.76	70.1	3.31	82.0	---
	6WSBF6-SS	3/4" - 14 BSPP	A.I. 316	2.76	70.1	3.31	82.0	---
	6WSOF6	1-1/16" - 12 ORB	Acero	2.76	70.1	3.31	82.0	---
1"	8WSF8	1" - 11-1/2 NPTF	Acero	3.45	87.6	4.10	101.6	---
	8WSF8-SS	1" - 11-1/2 NPTF	A.I. 316	3.45	87.6	4.10	101.6	---
	8WSBF8	1" - 11 BSPP	Acero	3.45	87.6	4.10	101.6	---
	8WSBF8-SS	1" - 11 BSPP	A.I. 316	3.45	87.6	4.10	101.6	---
	8WSOF8	1-5/16" - 12 ORB	Acero	3.45	87.6	4.10	101.6	---
1-1/4"	10WSF10	1-1/4" - 11-1/2 NPTF	Acero	4.40	111.8	4.78	118.1	---
	10WSF10-SS	1-1/4" - 11-1/2 NPTF	A.I. 316	4.40	111.8	4.78	118.1	---
	10WSBF10	1-1/4" - 11 BSPP	Acero	4.40	111.8	4.78	118.1	---
	10WSBF10-SS	1-1/4" - 11 BSPP	A.I. 316	4.40	111.8	4.78	118.1	---
	10WSOF10	1-5/8" - 12 ORB	Acero	4.40	111.8	4.78	118.1	---
1-1/2"	12WSF12	1-1/2" - 11-1/2 NPTF	Acero	5.13	130.3	5.68	137.9	---
	12WSF12-SS	1-1/2" - 11-1/2 NPTF	A.I. 316	5.13	130.3	5.68	137.9	---
	12WSBF12	1-1/2" - 11 BSPP	Acero	5.13	130.3	5.68	137.9	---
	12WSBF12-SS	1-1/2" - 11 BSPP	A.I. 316	5.13	130.3	5.68	137.9	---
	12WSOF12	1-7/8" - 12 ORB	Acero	5.13	130.3	5.68	137.9	---
2"	16WSF16	2" - 11-1/2 NPTF	Acero	6.09	154.7	6.90	170.9	---
	16WSF16-SS	2" - 11-1/2 NPTF	A.I. 316	6.09	154.7	6.90	170.9	---
	16WSBF16	2" - 11 BSPP	Acero	6.09	154.7	6.90	170.9	---
	16WSBF16-SS	2" - 11 BSPP	A.I. 316	6.09	154.7	6.90	170.9	---
	16WSOF16	2-1/2" - 12 ORB	Acero	6.09	154.7	6.90	170.9	---



Acero



Acero inoxidable 316



Ejemplo de Cople Serie-WS con puerto de inspección.



Ejemplo de Cople WS con caras planas para ajuste de llave de tuerca
* Las caras planas para llave de tuerca pueden resultar en un desempeño de menor presión.