


**Codos de Asiento Biselado**

**Codo 90° Asiento Biselado Roscado x Asiento Biselado Roscado - B2C**



D.E. Tubing	A (in)	Acero Inoxidable 304 # de Parte
1"	2.22	B2C-G100
1-1/2"	2.97	B2C-G150
2"	3.75	B2C-G200
2-1/2"	4.63	B2C-G250
3"	5.41	B2C-G300
4"	7.03	B2C-G400



**Codo 90° Asiento Biselado Roscado x Asiento Plano Biselado con Tuerca Hexagonal - B2F**




D.E. Tubing	A (in)	Acero Inoxidable 304 # de Parte
1"	2.22	B2F-G100
1-1/2"	2.97	B2F-G150
2"	3.75	B2F-G200
2-1/2"	4.63	B2F-G250
3"	5.41	B2F-G300
4"	7.03	B2F-G400



**Codo 90° Asiento Plano Biselado x Asiento Plano Biselado con Tuerca Hexagonal - B2E**



D.E. Tubing	A (in)	Acero Inoxidable 304 # de Parte
1"	2.22	B2E-G100
1-1/2"	2.97	B2E-G150
2"	3.75	B2E-G200
2-1/2"	4.63	B2E-G250
3"	5.41	B2E-G300
4"	7.03	B2E-G400



**N**

**Codo 45° Asiento Biselado Roscado x Asiento Plano Biselado con Tuerca Hexagonal - B2P**



D.E. Tubing	A (in)	Acero Inoxidable 304 # de Parte
1"	1.34	B2P-G100
1-1/2"	1.66	B2P-G150
2"	2.00	B2P-G200
2-1/2"	2.44	B2P-G250
3"	2.78	B2P-G300
4"	3.53	B2P-G400

