


Soportes Hexagonales para Tubing

Soportes Hexagonales con Manga de Polipropileno - B24PS

Especificación:

- Temperatura máxima de manga de polipropileno: 230°F (110°C).

D.E. Tubing	A (in)	B (in)	Acero Inoxidable 304 # de Parte
1/2"	2.80	1.15	B24PS-G50
3/4"	2.80	1.15	B24PS-G75
1"	3.43	1.45	B24PS-G100
1-1/2"	4.00	2.13	B24PS-G150
2"	4.50	2.50	B24PS-G200
2-1/2"	4.95	3.13	B24PS-G250
3"	5.50	3.75	B24PS-G300
4"	6.95	4.75	B24PS-G400
5"	8.06	5.63	B24PS-G500
6"	9.25	6.63	B24PS-G600
8"	11.50	8.63	B24PS-G800
10"	14.50	10.50	B24PS-G1000
12"	16.63	13.00	B24PS-G1200




NOTA: Opción de detección por metal disponible.

Soportes Hexagonales con Manga de Polisulfona para Alta Temperatura - B24HS

Especificación:

- Temperatura máxima para manga de alta temperatura: 325°F (163°C).

D.E. Tubing	A (in)	B (in)	Acero Inoxidable 304 # de Parte
1/2"	2.38	1.06	B24HS-G50
3/4"	2.63	1.19	B24HS-G75
1"	2.69	1.56	B24HS-G100
1-1/2"	3.63	2.13	B24HS-G150
2"	4.63	2.63	B24HS-G200
2-1/2"	4.81	3.13	B24HS-G250
3"	5.38	3.63	B24HS-G300
4"	6.63	4.63	B24HS-G400
6"	9.00	6.63	B24HS-G600



NOTA: La manga debe removerse antes de soldarse.

