

**Soportes Hexagonales para Tubing**

**Mangas - 13PS**

**Especificaciones:**


- Temperatura máxima para mangas de polipropileno: 230°F (110°C)
- Temperatura máxima para manga de alta temperatura: 325°F (163°C)



Polipropileno



Alta temperatura



| Medida | Polipropileno<br># de Parte | Alta Temperatura<br># de Parte |
|--------|-----------------------------|--------------------------------|
| 1/2"   | 13PS-50                     | 13HS-50                        |
| 3/4"   | 13PS-75                     | 13HS-75                        |
| 1"     | 13PS-100                    | 13HS-100                       |
| 1-1/2" | 13PS-150                    | 13HS-150                       |
| 2"     | 13PS-200                    | 13HS-200                       |
| 2-1/2" | 13PS-250                    | 13HS-250                       |
| 3"     | 13PS-300                    | 13HS-300                       |
| 4"     | 13PS-400                    | 13HS-400                       |
| 5"     | 13PS-500                    | ---                            |
| 6"     | 13PS-600                    | 13HS-600                       |
| 8"     | 13PS-800                    | ---                            |

NOTA: Opción de detección por metal disponible.

**Soporte Redondo con Insertos de Nitrilo - B24RPH**


**Características:**

- Todos los soportes colgantes hexagonales y redondos pueden ser equipados con las siguientes opciones de cople: 3/8" NPT o conexión de paso directo; 3/8"-16 o 1/2"-13 disponible bajo pedida.



**Especificación:**

- Máxima temperatura para insertos de nitrilo: 230°F (110°C).



| D.E.<br>Tubing | A<br>(in) | B<br>(in) | Acero Inoxidable 304<br># de Parte |
|----------------|-----------|-----------|------------------------------------|
| 1/2"           | 2.75      | 1.13      | B24RPH-G50                         |
| 3/4"           | 2.75      | 1.13      | B24RPH-G75                         |
| 1"             | 3.31      | 1.50      | B24RPH-G100                        |
| 1-1/2"         | 3.81      | 2.00      | B24RPH-G150                        |
| 2"             | 4.25      | 2.56      | B24RPH-G200                        |
| 2-1/2"         | 5.00      | 3.00      | B24RPH-G250                        |
| 3"             | 5.50      | 3.56      | B24RPH-G300                        |
| 4"             | 6.50      | 4.69      | B24RPH-G400                        |

N