

Adaptador Hembra x Macho - Oreja de Balancín (continuado)

Estilo N37

Esta tabla es continuación de la página anterior.



Reductor



misma medida



Incrementador

| Rosca Hembra | Rosca Macho | Extrusión Aluminio Anodizado # de Parte |
|--------------|--------------|---|
| 2½" NST (NH) | ¾" GHT | N37-25F07G |
| | ¾" NPT | N37-25F07T |
| | 1" NPT | N37-25F10T |
| | 1½" NST (NH) | N37-25F15F |
| | 1½" NPSH | N37-25F15S |
| | 1½" NPT | N37-25F15T |
| | 2" NPT | N37-25F20T |
| | 2½" NST (NH) | N37-25F25F |
| | 2½" NPSH | N37-25F25S |
| | 2½" NPT | N37-25F25T |
| | 3" NST (NH) | N37-25F30F |
| 3" NPT | N37-25F30T | |
| 2½" NPSH | 1½" NPSH | N37-25S15S |
| | 2½" NST (NH) | N37-25S25F |
| | 2½" NPT | N37-25S25T |
| 2½" NPT | 1½" NPSH | N37-25T15S |
| | 2½" NST (NH) | N37-25T25F |
| | 3" NPT | N37-25T30T |
| 3" NST (NH) | 1½" NST (NH) | N37-30F15F |
| | 2½" NST (NH) | N37-30F25F |
| | 3" NPT | N37-30F30T |
| 3" NPT | 2½" NST (NH) | N37-30S25F |
| | 2½" NST (NH) | N37-30T25F |
| | 2½" NPT | N37-30T25T |
| 4" NST (NH) | 2½" NST (NH) | N37-40F25F |
| | 4" NST (NH) | N37-40F40F |
| | 4" NPT | N37-40F40T |
| 4" NPT | 6" NST (NH) | N37-40F60F |
| | 2½" NST (NH) | N37-40T25F |
| | 4" NST (NH) | N37-40T40F |
| 4½" NST (NH) | 4½" NST (NH) | N37-40T45F |
| | 2½" NST (NH) | N37-45F25F |
| | 4" NST (NH) | N37-45F40F |
| 5" NST (NH) | 4" NPT | N37-45F40T |
| | 5" NST (NH) | N37-45F50F |
| | 4½" NST (NH) | N37-50F45F |
| 5" NPSH | 5" NPT | N37-50F50T |
| | 6" NST (NH) | N37-50F60F |
| | 6" NST (NH) | N37-50S60F |
| 6" NST (NH) | 5" NPT | N37-50T50F |
| | 4" NPT | N37-60F40T |
| | 5" NST (NH) | N37-60F50F |
| 6" NPT | 6" NPT | N37-60F60T |
| | 4" NST (NH) | N37-60T40F |
| | 6" NST (NH) | N37-60T60F |

Todos los adaptadores se fabrican bajo las especificaciones Dixon®. Arandelas de reemplazo pueden encontrarse en las páginas 943.